

RF-Link/Araneus USA, Inc. PRELIMINARY SPECIFICATIONS

V200N00XXX

5.8GHz TRANSMITTER

RF OUTPUT @ CONNECTOR	- 4 ~ 0 dBm
CHANNEL FREQUENCY	CH 1 - 5745 MHz CH 2 - 5765 MHz CH 3 - 5785 MHz CH 4 - 5805 MHz
FREQUENCY STABILITY	± 350 KHz
OPERATING DISTANCE	5 ~ 100 M LINE OF SIGHT
DC POWER INPUT	10.8 ~ 16 VDC
DC INPUT CURRENT CONSUMPTION	< 500 mA
VIDEO INPUT	NTSC 1Vp-p @ 75 OHM PRE-EMPHASIS NTSC
AUDIO INPUT	LEVEL : 2 Vp-p @ 600 OHM PRE-EMPHASIS : 75uS
AUDIO FREQUENCY RESPONSE	30 Hz ~12 KHz (3dB BW)
JACKS' COLOR	VIDEO : YELLOW AUDIO (LEFT) : WHITE AUDIO (RIGHT) : RED
OPERATION TEMPERATURE	0 °C to 50 °C, INDOOR USE ONLY
STORAGE TEMPERATURE	-20 °C to 70 °C

Model#	V200N00XXX	
Des.	SPECIFICATIONS	
SIZE A	A0042 3702	Rev. 0A
Date	Jan . 6 . 2003	

Approved by: Prepared by :